



Ralph Amissah

copy @ www.jus.uio.no/sisu/ *

Copyright © Ralph Amissah 2007, part of SiSU documentation,
License GPL 3

Generated by [SiSU](#) [SiSU 0.59.1 of 2007w39/2] www.jus.uio.no/sisu

Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is software for document structuring, publishing and search (with object citation
numbering), www.sisudoc.org

SiSU is released under [GPL 3](#) or later, <<http://www.fsf.org/licenses/gpl.html>>.

Document information:

sourcefile sisu_search.sst

Generated by [SiSU](#) www.jus.uio.no/sisu

version information: [SiSU 0.59.1 of 2007w39/2](#)

For alternative output formats of this document check:

<http://www.jus.uio.no/sisu/sisu_search/sisu_manifest.html>

Contents

SiSU - Search, Ralph Amissah	1
SiSU Search	1
1. SiSU Search - Introduction	1
2. SQL	2
2.1 populating SQL type databases	2
3. Postgresql	3
3.1 Name	3
3.2 Description	3
3.3 Synopsis	3
3.4 Commands	3
4. Sqlite	4
4.1 Name	4
4.2 Description	4
4.3 Synopsis	4
4.4 Commands	4
5. Introduction	5
5.1 Search - database frontend sample, utilising database and SiSU features, including object citation num- bering (backend currently PostgreSQL)	5
5.2 Search Form	5
6. Hyperestraier	6
Document Information (metadata)	8
Metadata	8
Information on this document copy and an unofficial List of Some web related information and sources	9
Information on this document copy	9
Links that may be of interest	9

1 **SiSU - SEARCH,
RALPH AMISSAH**

2 **SiSU SEARCH**

3 **1. SiSU Search - Introduction**

4 SiSU output can easily and conveniently be indexed by a number of stand-alone indexing tools, such as Lucene, Hyperestraier.

5 Because the document structure of sites created is clearly defined, and the text object citation system is available hypothetically at least, for all forms of output, it is possible to search the sql database, and either read results from that database, or just as simply map the results to the html output, which has richer text markup.

6 In addition to this SiSU has the ability to populate a relational sql type database with documents at an object level, with objects numbers that are shared across different output types, which make them searchable with that degree of granularity. Basically, your match criteria is met by these documents and at these locations within each document, which can be viewed within the database directly or in various output formats.

7 2. SQL

8 2.1 populating SQL type databases

9 SiSU feeds sisu markupd documents into sql type databases PostgreSQL¹
 and/or SQLite² database together with information related to document
 structure.

10 This is one of the more interesting output forms, as all the structural data
 of the documents are retained (though can be ignored by the user of the
 database should they so choose). All site texts/documents are (currently)
 streamed to four tables:

- 11 • one containing semantic (and other) headers, including, title, au-
 thor, subject, (the Dublin Core...);
- 12 • another the substantive texts by individual “paragraph” (or object)
 - along with structural information, each paragraph being identifi-
 able by its paragraph number (if it has one which almost all of them
 do), and the substantive text of each paragraph quite naturally being
 searchable (both in formatted and clean text versions for searching);
 and
- 13 • a third containing endnotes cross-referenced back to the paragraph
 from which they are referenced (both in formatted and clean text ver-
 sions for searching).
- 14 • a fourth table with a one to one relation with the headers table
 contains full text versions of output, eg. pdf, html, xml, and ascii.

15 There is of course the possibility to add further structures.

¹ <<http://www.postgresql.org/>>
 <<http://advocacy.postgresql.org/>>
 <<http://en.wikipedia.org/wiki/Postgresql>>

² <<http://www.hwaci.com/sw/sqlite/>>
 <<http://en.wikipedia.org/wiki/Sqlite>>

At this level SiSU loads a relational database with documents chunked
 into objects, their smallest logical structurally constituent parts, as text ob-
 jects, with their object citation number and all other structural information
 needed to construct the document. Text is stored (at this text object level)
 with and without elementary markup tagging, the stripped version being
 so as to facilitate ease of searching.

Being able to search a relational database at an object level with the SiSU
 citation system is an effective way of locating content generated by SiSU . As individual text objects of a document stored (and indexed) together
 with object numbers, and all versions of the document have the same num-
 ber, complex searches can be tailored to return just the locations of the
 search results relevant for all available output formats, with live links to
 the precise locations in the database or in html/xml documents; or, the
 structural information provided makes it possible to search the full con-
 tents of the database and have headings in which search content appears,
 or to search only headings etc. (as the Dublin Core is incorporated it is
 easy to make use of that as well).

18 3. Postgresql

19 3.1 Name

20 **SiSU** - Structured information, Serialized Units - a document publishing
system, postgresql dependency package

21 3.2 Description

22 Information related to using postgresql with sisu (and related to the
sisu_postgresql dependency package, which is a dummy package to in-
stall dependencies needed for **SiSU** to populate a postgresql database,
this being part of **SiSU** - man sisu).

23 3.3 Synopsis

24 sisu -D [instruction] [filename/wildcard if required]

25 sisu -D -pg -[instruction] [filename/wildcard if required]

26 3.4 Commands

27 Mappings to two databases are provided by default, postgresql and
sqlite, the same commands are used within sisu to construct and populate
databases however -d (lowercase) denotes sqlite and -D (uppercase)
denotes postgresql, alternatively –sqlite or –pgsql may be used

28 **-D or –pgsql** may be used interchangeably.

29 3.4.1 create and destroy database

30 –pgsql –createall

initial step, creates required relations (tables, indexes) in existing (post-
gresql) database (a database should be created manually and given the
same name as working directory, as requested) (rb.dbi)

31 **sisu -D –createdb**

creates database where no database existed before

32 **sisu -D –create**

creates database tables where no database tables existed before

33 **sisu -D –Dropall**

destroys database (including all its content)! kills data and drops tables,
indexes and database associated with a given directory (and directories of
the same name).

34 **sisu -D –recreate**

destroys existing database and builds a new empty database struc-
ture

35 3.4.2 import and remove documents

36 **sisu -D –import -v [filename/wildcard]**

populates database with the contents of the file. Imports documents(s)
specified to a postgresql database (at an object level).

37 **sisu -D –update -v [filename/wildcard]**

updates file contents in database

38 **sisu -D –remove -v [filename/wildcard]**

removes specified document from postgresql database.

39 4. Sqlite

40 4.1 Name

41 **SiSU** - Structured information, Serialized Units - a document publishing
system.

42 4.2 Description

43 Information related to using sqlite with sisu (and related to the sisu_sqlite
dependency package, which is a dummy package to install dependencies
needed for **SiSU** to populate an sqlite database, this being part of **SiSU** -
man sisu).

44 4.3 Synopsis

```
45     sisu -d [instruction] [filename/wildcard if required]
46     sisu -d -(sqlite|pg) -[instruction] [filename/wildcard if required]
```

47 4.4 Commands

48 Mappings to two databases are provided by default, postgresql and
sqlite, the same commands are used within sisu to construct and populate
databases however -d (lowercase) denotes sqlite and -D (uppercase)
denotes postgresql, alternatively –sqlite or –pgsql may be used

49 **-d or –sqlite** may be used interchangeably.

50 4.4.1 create and destroy database

51 –sqlite –createall

initial step, creates required relations (tables, indexes) in existing (sqlite)
database (a database should be created manually and given the same name
as working directory, as requested) (rb.dbi)

52 **sisu -d –createdb**

creates database where no database existed before

53 **sisu -d –create**

creates database tables where no database tables existed before

54 **sisu -d –dropall**

destroys database (including all its content)! kills data and drops tables,
indexes and database associated with a given directory (and directories of
the same name).

55 **sisu -d –recreate**

destroys existing database and builds a new empty database struc-
ture

56 4.4.2 import and remove documents

57 **sisu -d –import -v [filename/wildcard]**

populates database with the contents of the file. Imports documents(s)
specified to an sqlite database (at an object level).

58 **sisu -d –update -v [filename/wildcard]**

updates file contents in database

59 **sisu -d –remove -v [filename/wildcard]**

removes specified document from sqlite database.

60

5. Introduction

61

5.1 Search - database frontend sample, utilising database and SiSU features, including object citation numbering (backend currently PostgreSQL)

62

Sample search frontend ³ A small database and sample query frontend (search from) that makes use of the citation system, object citation numbering to demonstrates functionality.⁴

63

SiSU can provide information on which documents are matched and at what locations within each document the matches are found. These results are relevant across all outputs using object citation numbering, which includes html, XML, LaTeX, PDF and indeed the SQL database. You can then refer to one of the other outputs or in the SQL database expand the text within the matched objects (paragraphs) in the documents matched.

64

Note you may set results either for documents matched and object number locations within each matched document meeting the search criteria; or display the names of the documents matched along with the objects (paragraphs) that meet the search criteria.⁵

65

sisu -F –webserv-webrick

builds a cgi web search frontend for the database created

66

The following is feedback on the setup on a machine provided by the help

³ <<http://search.sisudoc.org>>

⁴ (which could be extended further with current back-end). As regards scaling of the database, it is as scalable as the database (here Postgresql) and hardware allow.

⁵ of this feature when demonstrated to an IBM software innovations evaluator in 2004 he said to paraphrase: this could be of interest to us. We have large document management systems, you can search hundreds of thousands of documents and we can tell you which documents meet your search criteria, but there is no way we can tell you without opening each document where within each your matches are found.

command:

sisu –help sql

```
Postgresql
user:      ralph
current db set: SiSU_sisu
port:      5432
dbi connect: DBI:Pg:database=SiSU_sisu;port=5432
sqlite
current db set: /home/ralph/sisu_www/sisu/sisu_sqlite.db
dbi connect DBI:SQLite:/home/ralph/sisu_www/sisu/sisu_sqlite.db
```

Note on databases built

By default, [unless otherwise specified] databases are built on a directory basis, from collections of documents within that directory. The name of the directory you choose to work from is used as the database name, i.e. if you are working in a directory called /home/ralph/ebook the database SiSU_ebook is used. [otherwise a manual mapping for the collection is necessary]

5.2 Search Form

sisu -F

generates a sample search form, which must be copied to the web-server cgi directory

sisu -F –webserv-webrick

generates a sample search form for use with the webrick server, which must be copied to the web-server cgi directory

sisu -Fv

as above, and provides some information on setting up hyperestraier

sisu -W

starts the webrick server which should be available wherever sisu is properly installed

The generated search form must be copied manually to the webserver
76 directory as instructed

6. Hyperestraier

See the documentation for hyperestraier:

<<http://hyperestraier.sourceforge.net/>>

/usr/share/doc/hyperestraier/index.html

man estcmd

on sisu_hyperestraier:

man sisu_hyperestraier

/usr/share/doc/sisu/sisu_markup/sisu_hyperestraier/index.html

NOTE: the examples that follow assume that sisu output is placed in the
85 directory /home/ralph/sisu_www

(A) to generate the index within the webserver directory to be in-
86 dexed:

estcmd gather -sd [index name] [directory path to index]

the following are examples that will need to be tailored according to your
88 needs:

cd /home/ralph/sisu_www

estcmd gather -sd casket /home/ralph/sisu_www

you may use the ‘find’ command together with ‘egrep’ to limit indexing
91 to particular document collection directories within the web server direc-
tory:

```
find /home/ralph/sisu_www -type f | egrep '/home/ralph/sisu_www/sisu/\w+?.htm  
|estcmd gather -sd casket -
```

Check which directories in the webserver/output directory (~ /sisu_www
93 or elsewhere depending on configuration) you wish to include in the search
index.

As sisu duplicates output in multiple file formats, it is probably prefer-
94

able to limit the estraier index to html output, and as it may also be desirable to exclude files ‘plain.txt’, ‘toc.html’ and ‘concordance.html’, as these duplicate information held in other html output e.g.

95 find /home/ralph/sisu_www -type f | egrep '/sisu_www/(sisu|bookmarks)/.+?.html\$'
| egrep -v '(doc|concordance).html\$' |estcmd gather -sd casket -

96 from your current document preparation/markup directory, you would
construct a rune along the following lines:

97 find /home/ralph/sisu_www -type f | egrep '/home/ralph/sisu_www/([specify
first directory for inclusion]| [specify second directory for
inclusion]| [another directory for inclusion? ...])/.+?.html\$'
| egrep -v '(doc|concordance).html\$' |estcmd gather -sd
/home/ralph/sisu_www/casket -

98 (B) to set up the search form

99 (i) copy estseek.cgi to your cgi directory and set file permissions to
755:

100 sudo cp -vi /usr/lib/estraier/estseek.cgi /usr/lib/cgi-bin
101 sudo chmod -v 755 /usr/lib/cgi-bin/estseek.cgi
102 sudo cp -v /usr/share/hyperestraier/estseek.* /usr/lib/cgi-bin
103 [see estraier documentation for paths]

104 (ii) edit estseek.conf, with attention to the lines starting ‘indexname:’ and
‘replace:’:

105 indexname: /home/ralph/sisu_www/casket
106 replace: *file* : //*home/ralph/sisu_www{!}*
107 replace: /index.html?\${{!}}/

108 (C) to test using webrick, start webrick:

109 sisu -W

110 and try open the url: <<http://localhost:8081/cgi-bin/estseek.cgi>>

DOCUMENT INFORMATION (METADATA)

Metadata

Document Manifest @

<http://www.jus.uio.no/sisu/sisu_manual/sisu_search/sisu_manifest.html>

Dublin Core (DC)

DC tags included with this document are provided here.

DC Title: [SiSU - Search](#)

DC Creator: [Ralph Amissah](#)

DC Rights: [Copyright \(C\) Ralph Amissah 2007, part of SiSU documentation, License GPL 3](#)

DC Type: [information](#)

DC Date created: [2002-08-28](#)

DC Date issued: [2002-08-28](#)

DC Date available: [2002-08-28](#)

DC Date modified: [2007-09-16](#)

DC Date: [2007-09-16](#)

Version Information

Sourcefile: [sisu_search.sst](#)

Filetype: [SiSU text insert 0.58](#)

Sourcefile Digest, MD5(sisu_search.sst)= [c085c2eb6d68f1b7d50435f673ede407](#)

Skin_Digest: MD5(/home/ralph/grotto/theatre/dbld/builds/sisu/sisu/data/doc/sisu/sisu_markup_samples/sisu_manual/_sisu/skin/doc/skin_sisu_manual.rb)=
[20fc43cf3eb6590bc3399a1aef65c5a9](#)

Generated

Document (metaverse) last generated: [Tue Sep 25 02:54:29 +0100 2007](#)

Generated by: [SiSU 0.59.1](#) of 2007w39/2 (2007-09-25)

Ruby version: [ruby 1.8.6 \(2007-06-07 patchlevel 36\) \[i486-linux\]](#)

Information on this document copy and an unofficial List of Some web related information and sources

”Support Open Standards and Software Libre for the Information Technology Infrastructure” RA

Information on this document copy www.jus.uio.no/sisu/

Generated by **SiSU** found at www.jus.uio.no/sisu [SiSU 0.59.1 2007w39/2] www.sisudoc.org.
 SiSU is software for document structuring, publishing and search (using SiSU: object citation numbering, markup, meta-markup, and system) Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is released under [GPL 3](http://www.fsf.org/licenses/gpl.html) or later (www.fsf.org/licenses/gpl.html).

W3 since October 3 1993  SiSU 1997, current 2007.
SiSU presentations at www.jus.uio.no/sisu/

SiSU **pdf** versions can be found at:

http://www.jus.uio.no/sisu/sisu_search/portrait.pdf
http://www.jus.uio.no/sisu/sisu_search/landscape.pdf

SiSU **html** versions may be found at:

http://www.jus.uio.no/sisu/sisu_search/toc.html OR
http://www.jus.uio.no/sisu/sisu_search/doc.html

SiSU Manifest of document output and metadata may be found at:

http://www.jus.uio.no/sisu/sisu_search/sisu_manifest.html

SiSU found at: www.jus.uio.no/sisu/

Links that may be of interest at SiSU and elsewhere:

SiSU Manual

http://www.jus.uio.no/sisu/sisu_manual/

Book Samples and Markup Examples

<http://www.jus.uio.no/sisu/SiSU/2.html>

SiSU @ Wikipedia

<http://en.wikipedia.org/wiki/SiSU>

SiSU @ Freshmeat

<http://freshmeat.net/projects/sisu/>

SiSU @ Ruby Application Archive

<http://raa.ruby-lang.org/project/sisu/>

SiSU @ Debian

<http://packages.qa.debian.org/s/sisu.html>

SiSU Download

<http://www.jus.uio.no/sisu/SiSU/download.html>

SiSU Changelog

<http://www.jus.uio.no/sisu/SiSU/changelog.html>

SiSU help

http://www.jus.uio.no/sisu/sisu_manual/sisu_help/

SiSU help sources

http://www.jus.uio.no/sisu/sisu_manual/sisu_help_sources/

SiSU home:

www.jus.uio.no/sisu/